

Certificate of compliance

with the order 2.1 according to EN 10 204

LifY

We confirm that the above mentioned **PVC single core** is produced **in alignment with DIN VDE 0250, DIN VDE 0285-525-1 / DIN EN 50525-1** and tested according to DIN EN 50395, DIN EN 50396.

TECHNICAL DATA

Temperature range	flexible -15°C to +80°C
Nominal voltage	0.5 - 1 mm ² : AC U ₀ /U 300/500 V 1.5 - 70 mm ² : AC U ₀ /U 450/750 V
Peak operating voltage	0.1 - 0.25 mm ² : 300 V (not for high power current installation purposes)

TESTS

flame-retardant acc. to DIN VDE 0482-332-1-2 / DIN EN 60332-1-2 / IEC 60332-1-2
certifications and approvals:
EAC

PROPERTIES

the materials used during manufacturing are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers



Product conforms with Low-Voltage Directive 2014/35/EU

HELU KABEL GmbH
Technical Department

This document is valid without signature

Date of issue
29.08.2022

Date of expiration
31.12.2023

Point of Contact
Christian Dettmer
Tel. +49 7150 9209-712
techsupport@helukabel.de
helukabel.com

HELU KABEL GmbH
Headquarters
Schloßhaldenstraße 10
71282 Hemmingen
Germany